



QuickSeam™ FormFlash™

1. Description

The Firestone QuickSeam™ FormFlash™ is a 152 mm (6"), 229 mm (9"), 305 mm (12") or 450 mm (18") uncured EPDM strip factory-laminated to QuickSeam Tape. The strip is designed to flash inside and outside corners, pipes, penetrations and other applications as specified in the Firestone guidelines.



2. Preparation

The RubberGard™ EPDM surfaces and/or mating surfaces must be prepared with QuickPrime™ Plus, using a QuickScrubber™. Use of other products is not allowed. Restore the product to room temperature prior to use if exposed to temperatures below 15°C for prolonged periods.

3. Application

On cloudy days with ambient temperature below 15°C, the use of a heat gun is recommended to warm the QuickSeam FormFlash and to ensure good formability. Refer to the Firestone guidelines for specific installation instructions.

Note: QuickSeam FormFlash is a non-vulcanized product and cures after installation. Correct use, accurate installation technique and installation according general roofing practice will result the final characteristics and proper functioning of the product.

4. Coverage

In accordance with length of detail.

5. Characteristics

Technical	EPDM Flashing	QuickSeam Tape
• Base	EPDM	Rubber polymers
• Color	Black	Black
• Solvents	None	None
• Solids	100%	100%
• State	Uncured	Cured
• Thickness	1.6 mm	0.6 mm
• Width	152 mm - 229 mm - 305 mm - 450 mm	156 mm - 235 mm - 311 mm - 456 mm

6. Packaging / Storage / Shelf Life

Packaging	15.25 m (50') rolls, 2 rolls per carton (6" and 9") - 1 roll per carton (12" and 18")
Part numbers	<ul style="list-style-type: none"> • W56RAC0650 (6") • W56RAC1650 (9") • W56RAC1653 (12") • W56RAC162A (18")

Note: QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.

Storage: Store in original unopened containers at temperatures between 15°C and 25°C, in a well-ventilated place. Keep the material dry and out of direct sunlight until ready for application.

Technical Information Sheet



Shelf Life: 12 months, when stored in above-mentioned conditions. Verify production date on each roll. Shelf life will be reduced if exposed to higher temperatures. Shelf life information is only a recommendation and not a fact of life. The real expiration date highly depends on the history of storage and handling of the accessories.

7. Precautions

Refer to Safety Data Sheets.

This document replaces any other document published previous. This sheet is meant to highlight Firestone product information based on latest knowledge and experience and is subject to change without notice (check the Firestone website for latest document version). Above mentioned values are based on tested samples and may vary within applicable tolerances. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. No Firestone representative is authorized to vary this disclaimer.